

## 36" 5 Induction Zones Rangetop Stainless Steel Professional Series

\$ 3,899



### **PROF365IRTXT**

This 36 inch Bertazzoni induction rangetops put Italian design and precision at the heart of the kitchen. While inspired by the commercial cooking this model features all the attributes of a residential kitchen design by sitting virtually flush with countertops and cabinets.

The 5 induction zones spaciouly is laid out to accommodate cookware of different sizes. Precision controls for each induction zone and feedback through the below glass digital display, create a highly intuitive cooking experience. The convenient bridge function on the 2 right-side area accommodates extra-large cookware. A timer, cookware detection and residual heat sensor complete the available features.

Easy cleaning of the cooking surface of the smooth surface make this range top even more compelling.

Bertazzoni rangetops are covered by an industry-leading 2-year parts and labor warranty and manufactured with pride in Italy.

[Guarda online](#)

# Specifications

---

## Features

---

### Worktop

---

|                           |   |
|---------------------------|---|
| Size                      | 36 in                                     |
| Number of induction zones | 5   |
| Worktop type              | electric                                  |
| Worktop design            | tempered glass with stainless steel frame |
| Worktop controls          | knobs                                     |
| Knobs                     | solid metal                               |

---

### Cooking zones

---

|                       |                                   |
|-----------------------|-----------------------------------|
| Rapid burner          | 10400 BTU (1)                     |
| Induction front left  | Ø 5 3/4 in 1400W (2200 W booster) |
| Induction back left   | Ø 8 1/4 in 2300W (3700 W booster) |
| Induction center      | Ø 8 1/4" 2300W (3700 W booster)   |
| Induction front right | Ø 9 1/2" 2100W (3700 W booster)   |
| Induction back right  | Ø 9 1/2" 2100W (3700 W booster)   |

---

### Technical specifications

---

|                   |  |
|-------------------|--|
| Electrical supply | 208 V 60 Hz - 10 000 / W 240 V 60 HZ - 11 500 W / 50 Amp |
| Power connection  | hardwired with 59" power cord                            |
| Certification     | UL   |

---

---

# Dimensions

---

TOP VIEW

